



Network

Dome

SNV-L6013R

2M H.264 Dome Camera



Key Features

- Max. 2M (1920 x 1080) resolution
- 30fps@all resolutions (H.264)
- Built-in 3.6mm fixed lens
- H.264, MJPEG dual codec, Multiple streaming
- microSD/SDHC memory slot, PoE
- IR viewable 15m, IP66, IK10
- Hallway view support (Rotate 90°/270°)
- LDC support (Lens Distortion Correction)

SNV-L6013R

2M H.264 Dome Camera



Specifications

Video

Imaging Device	1/2.9" 2.19M CMOS
Resolution	1920x1080, 1280x960, 1280x720, 1024x768, 800x600, 720x576, 640x480, 320x240
Max. Framerate	H.264 : Max.30fps at all resolutions MJPEG : Max.1fps at 1920x1080, 1280x960, 1280x720, 1024x768, Max. 15fps at other resolution
Min. Illumination	Color: 0.15Lux(1/30sec, F1.8), 0.003Lux(2sec, F1.8) B/W: 0Lux(IR LED on)

Lens

Focal Length (Zoom Ratio)	3.6mm fixed focal
Max. Aperture Ratio	F1.8
Angular Field of View	H: 92.6° / V: 48.9° / D: 110.7°
Min. Object Distance	0.5m(1.64ft)
Focus Control	Fixed

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	±5° / 0°~67° / ±90°
---------------------------	---------------------

Operational

Camera Title	Displayed up to 15 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, DWDR, SDDR
Digital Noise Reduction	SSNR
Motion Detection	4ea, rectangular zones
Privacy Masking	6ea, rectangular zones
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC	Support
Electronic Shutter Speed	Minimum / Maximum / Anti flicker
Video Rotation	Flip, Mirror, Hallway view(90°/270°)
Analytics	Motion detection, Tempering
Alarm Triggers	Analytics
Alarm Events	File upload via FTP and e-mail Notification via e-mail SD/SDHC or NAS recording at event triggers
Audio In	Line in
IR Viewable Length	15m(49.21ft)

Network

Ethernet	RJ-45(10/100BASE-T)
----------	---------------------

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com

Hanwha Vision is formerly known as Hanwha Techwin.

Video Compression	H.264, MJPEG
Audio Compression	G.711 u-law / G.726 selectable G.726 (ADPCM) 8KHz, G.711 8KHz, G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
Bitrate Control	H.264: CBR or VBR MJPEG: VBR
Streaming	Unicast(6 users) / Multicast Multiple streaming(Up to 3 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP)
Application Programming Interface	ONVIF Profile S/G SUNAPI(HTTP API)

General

Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek, Norwegian, Finnish
Web Viewer	Supported OS : Windows 7, 8, 10, Mac OS X 10.8, 10.9, 10.10, 10.11 Supported Browser : Explore 11, Mozilla Firefox 43, Apple Safari 9 * Mac OS X only
Edge Storage	Micro SD/SDHC 1slot

Environmental & Electrical

Operating Temperature / Humidity	-30°C ~ +55°C(-22°F ~ +131°F) / Less than 90% RH * Start up should be done at above -20°C(-4°F)
Storage Temperature / Humidity	-30°C ~ +60°C(-22°F ~ +140°F) / Less than 90% RH
Certification	IP66, IK10 EN55011:2009+A1:2010, EN50581:2012, EN50121-3-2:2015, EN61000-4-2:2009, EN61000-4-3:2006+A2:2010, EN61000-4.4:2012, EN61000-4-5:2014, EN61000-4-6:2009, EN50155:2007, NEMA 4x
Input Voltage	PoE(IEEE802.3af, Class2)
Power Consumption	Max. 5.80W

Mechanical

Color / Material	Ivory / Aluminum
Product Dimensions / Weight	98.9x52.0x100.0mm(3.89x2.05x3.94"), 295g(0.65 lb)